

## DESCRIPTION

- Protection class IP 68
- Entirely made of stainless steel 316Ti
- Round or square attachment cover, height 5mm
- Toughened safety glass (ESG)- withstands loads of up to 650 kg
- POWER-LED cold white, warm white, neutral white,blue
- Multichip POWER-LED RGB,RGBW
- Operating mode: constant current or constant voltage
- Rotationally symmetric light distribution
- Cable pressure sleeve, stainless steel 316Ti
- Supplied with 5m of UW-cable

### Toughened safety glass

- Height 8mm
- Efficiency>85%



IP 68

STAINLESS  
STEEL V4A  
1.4571  
316Ti

2700K  
3000k  
4000K

RGB

RGBW

FC

CE

RoHS



For accentuation in small swimming pools, whirlpools, jacuzzis and water bodies and water displays.

## Technical Parameters

	SC009A		SC009B		SC009C	
Power Consumption	Max. 3W	Max. 6W	Max. 9W	Max. 12W	Max. 15W	Max. 18W
Qty of LED	3PCS	6PCS	9PCS	12PCS	15PCS	18PCS
LED Type	CREE, ORSAM, LUMILEDS					
LED Source Luminous Efficacy	130Lm/w(2700K), 140Lm/w(3000K), 150Lm/w(4000K), 150Lm/w(6000K)					
CRI	Ra≥80					
CCT/Color	2700K、3000K、4000K、RGB、RGBW					
Lumen Maintenance	50,000 hrs L70 at 25°C					
Beam Angle	10°、25°、45°					
Input Voltage	350MA、700MA、24VDC					
Control	On/OFF、DMX512					
Material	Stainless Steel316 & Clear Tempered Glass Cover					
Size	φ72×33mm		φ102×33mm		φ124×33mm	
Weight	0.5Kg		1Kg		1.35Kg	
Mech impact protection	IK10					
Protection	IP68					
Operating Temperature	-20°C ~ 50°C / -4°F ~ 122°F					
Storage Temperature	-30° C ~ 80°C / -22°F ~ 176°F					
Certification	FCC, CE, ROHS, CCC					

## Dimensions

Unit: mm

