

## DESCRIPTION

- Protection class IP 68
- Entirely made of stainless steel 316Ti
- Round or square attachment cover,height 5mm
- Toughened safety glass(ESG)-withstands loads of up to 650 kg
- POWER-LED cold white,warm white,neutral white,blue
- Multichip POWER-LED RGB,RGBW
- Operating mode:constant current or constant voltage
- Rotationally symmetric light distribution
- Cable pressure sleeve,stainless steel 316Ti
- Supplied with 5m of UW-cable



For accentuation in small swimming pools, whirlpools, jacuzzis and water bodies and water displays.

## Technical Parameters

	LX-SC-001
Power Consumption	Max. 36W
Qty of LEDs	18PCS
LED Source	CREE、ORSAM、LUMILEDS
LED Source Luminous Efficacy	135Lm/w(3000K)、140Lm/w(4000K)、150Lm/w(6000K)
CRI	Ra≥80
CCT/Color	3000K、4500K、6000K、RGBW
Lumen Maintenance	50,000 hrs L70 at 25°C
Beam Angle	10°、30°
Input	24VDC, Max. 500MA@24VDC
Control	ON/OFF、DMX512、DALI
Materials	Stainless Steel 316 Ti & Tempered Glass
Size	∅182× H87mm
Weight	3.5kg
Mech impact protection	IK10
Protection	IP68
Operating Temperature	-20°C ~ 50°C / -4°F ~ 122°F
Storage Temperature	-30° C ~ 80°C / -22°F ~ 176°F
Certification	FCC、CE、ROHS、CCC

## Dimensions

Unit:mm

